

2011 RACE TIRE SPECIFICATIONS

# Hoosier<sup>®</sup>

## RACING TIRE



## NO WARRANTY POLICY

**HOOSIER RACING TIRE CORP.** offers racing tires for sale only upon the conditions and the terms contained in this disclaimer of liability and indemnity. Due to many varied and different conditions which Hoosier Racing Tires and Tubes are exposed and because of the manner in which racing is conducted, Hoosier Racing Tire Corp. makes absolutely **no warranty**, expressed or implied, as to the fitness for a general or particular purpose or of merchantability in connection with any offer of sale of Hoosier Racing Tires and tubes. **"HOOSIER RACING TIRES AND TUBES ARE SOLD AS IS."** Race tires are not tested or labeled to meet FMVSS 109, 119, 139 or ECE36 Safety Standards. Therefore it is dangerous and illegal to sell race tires for use on public highways. Any person selling Hoosier Racing Tires or Tubes for highway use agrees to indemnify and reimburse Hoosier Racing Tire Corp. for all loss, damage, or liability Hoosier Racing Tire Corp. may suffer because of such sales. Not applicable where prohibited by law. Not following these warnings can cause **SERIOUS PERSONAL INJURY OR DEATH**. For more information read tire labels, follow manufacturer's warnings as molded in tire sidewalls and visit [hoosiertire.com](http://hoosiertire.com).

## FREEZE WARNING

**Freeze Crack Advisory:** This advisory addresses proper storage and use of Hoosier tires in cold conditions. Hoosier Tires, especially asphalt and hard compound tires, may experience Rubber Cracking if the tires are transported, crushed, flexed or stressed when frozen. The following guidelines are provided to avoid this problem.

1. Always store Hoosier Racing Tires indoors at temperatures above 32° F.
2. If tires have been subject to 32° F or less, allow them to warm to room temperature (about 70° F) for a minimum of 24 hrs before the tire is mounted, transported or flexed.
3. Always use spare tires not intended for future competition to store vehicles for prolonged periods of time or winter transport.
4. If below freezing temperatures are expected, please consider shipping tires once more favorable conditions exist.

**Do not use tires that have evidence of Freeze Crack Damage.**

## WARNING

**Service Life for Race Tires:** Old tires can fail in use, causing loss of vehicle control and personal injury. Environmental conditions like temperature extremes, exposure to sunlight, electric arc, solvents, automotive fluids, and atmospheric pollutants accelerate the aging process. Hoosier Racing Tire strongly recommends that new (sticker) tires should be put in service within 2 years of date of purchase. Used (scuffed) tires have a shorter service life than new (sticker) tires. Poor storage and infrequent use accelerate the aging process.

## DIRECTION OF ROTATION / MOUNTING INSTRUCTIONS

### ROTATIONAL GUIDELINES FOR TIRES WITH DIRECTIONAL ARROWS

All Hoosier tires having directional arrows must be mounted so that the tire travels in the direction of the arrow. Hoosier tires having directional arrows will have them on both sidewalls. Directional arrows may not be on a tire that can have both left and/or right side application. All Hoosier tires not having directional arrows should be mounted as detailed below.

### ROTATIONAL GUIDELINES FOR TIRES WITHOUT DIRECTIONAL ARROWS

Every Hoosier race tire has a four character serial code embossed into ONE sidewall of the tire. All Hoosier DOT tires will also have two additional codes as required by the Department of Transportation. (Example: J7AB 4AX8 3710)

#### **CIRCLE TRACK RACING TIRES:**

(Includes both dirt and asphalt tires)

Hoosier tires must be mounted with the **serial code** located toward the infield.

#### **ROAD RACING TIRES:**

(Includes catalog numbers beginning with 43, 44, 45, 46)

In most cases, Hoosier tires used in Road Race applications should be mounted with the **serial code** toward the center of the vehicle. Once a tire has been run in the proper orientation it is acceptable to remount the tire in the opposite direction to even out the wear.

#### **DRAG RACING TIRES, INCLUDING DOT DRAG TIRES:**

(Includes catalog numbers beginning with 17, 18)

Hoosier drag tires can be mounted to rotate in either direction. Hoosier drag tires can also be flipped or reversed to provide even wear.

## WARNING TIRE MOUNTING IS DANGEROUS

**Special Tire Mounting Instructions:** Tire mounting should be done **only** by trained personnel using proper tools and procedures. Failure to follow safe mounting procedures could cause faulty positioning of the tire and cause the assembly to burst with explosive force sufficient to cause **SERIOUS PERSONAL INJURY OR DEATH**. Always inspect tire for kinked beads or other possible damage that may have occurred in shipping or storage. Clean rim and lubricate beads with rubber lubricant. Always lock rim on mounting machine or place in safety cage. Use a clip on chuck, an in-line valve with a pressure gauge or adjustable regulator and remote inflation/deflation device. Have enough air hose to stay out of the trajectory. Stand back.

## WARNING VERIFY RIM SIZE

**Verify Correct Wheel and Bead Flange:** All tires are designed to be used on wheels that are manufactured to Tire and Rim Association (T&RA) specifications and tolerances. Some rims are non-standard or damaged and it is necessary to inspect the rim flange to assure proper fit. Consult your specific rim manufacturer to determine if your rim can be used in this application. Never attempt to install and inflate a tire of one bead diameter on a rim or wheel of a different bead diameter. Use of Hoosier Racing Tires on wheels with incorrect bead flanges or wheels that do not meet T&RA standards can cause the assembly to fail and burst with explosive force sufficient to cause **SERIOUS PERSONAL INJURY OR DEATH**. Use a certified wheel rim disk tape to confirm wheel rim flange size.

## WARNING BEAD / RIM SEATING

When seating beads never exceed maximum bead seating pressure as molded in tire sidewall. Never exceed manufacturer's maximum inflation pressure. Always seat beads with wheel locked to mounting machine or placed in a safety cage. A damaged tire or wheel can fail during bead seating and burst with enough force sufficient to cause **SERIOUS PERSONAL INJURY OR DEATH**. Always use a clip on chuck, an in-line valve with a pressure gauge or adjustable regulator and remote inflation/deflation device. Have enough air hose to stay out of the trajectory. Stand back. If the beads will not seat at the manufacturer's maximum bead seating pressure, STOP, deflate tire, return the tire to the place of purchase.

## WARNING NOT FOR HIGHWAY USE

**NOT FOR HIGHWAY USE:** All Hoosier Racing Tires including DOT labeled Hoosier Racing Tires are designed for racing purposes only on specified racing surfaces and are **not to be operated on public roadways**. DOT labeled Hoosier Racing Tires meet Department Of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and **SERIOUS PERSONAL INJURY OR DEATH**.

Exception – "PRO STREET" page 20.

## WARNING MISUSE / MISAPPLICATION

**Application/Misuse:** All Hoosier Racing Tire products are designed for a specific purpose. Consult with Hoosier Racing Tire Corp. for specific fitment and application. Utilizing Hoosier Tires in any form outside of their intended use constitutes **misuse** of the product and can cause **SERIOUS PERSONAL INJURY OR DEATH**. Hoosier Racing Tire products are designed and manufactured for racing purposes only, within a closed course designed for organized competition. Not for recreational use. Hoosier Tires should never be used for Off Track Exhibition or for Land Speed Record Vehicles including Jet or Rocket Powered Cars.

## WARNING DO NOT ALTER TIRES

**Chemical Treatment of Tires:** Hoosier Racing Tires strictly forbids any chemical alteration of the tire carcass and/or tread compound such as tire "soaking" or use of tread "softener." Hoosier Racing Tire strictly forbids the physical defacement (removal, altering or covering), of tire sidewall markings in any manner. Failure to comply with this warning could result in premature or catastrophic tire failure and may result in **SERIOUS PERSONAL INJURY OR DEATH**.

# TREAD PATTERNS

TIRE TREADS

TIRE TREADS

<p>DRAGSTER FRONT</p>  <p>A</p>	<p>DRAG FRONT</p>  <p>B</p>	<p>DRAG SLICK</p>  <p>C</p>	<p>QUICK TIME PRO</p>  <p>D</p>
<p>RACING D.O.T. RADIAL</p>  <p>E</p>	<p>PRO STREET</p>  <p>F</p>	<p>VINTAGE</p>  <p>G</p>	<p>STREET TREAD</p>  <p>H</p>
<p>ROAD RACING WET</p>  <p>I</p>	<p>D.O.T. RADIAL WET</p>  <p>J</p>	<p>WRS-2</p>  <p>K</p>	<p>SUPER CHAIN LINK</p>  <p>L</p>
<p>RIB DIRT</p>  <p>M</p>	<p>IMCA</p>  <p>N</p>	<p>CROSSBLOCK</p>  <p>O</p>	<p>LARGE CROSSBLOCK</p>  <p>P</p>
<p>SMALL CROSSBLOCK</p>  <p>Q</p>	<p>RIB ASPHALT</p>  <p>R</p>	<p>CHECKERBOARD</p>  <p>S</p>	<p>LARGE CHECKERBOARD</p>  <p>T</p>

# TREAD PATTERNS

<p>ANGLE BLOCK</p>  <p>U</p>	<p>DIRT BOZZ STYLE</p>  <p>V</p>	<p>STAGGER BLOCK</p>  <p>W</p>	<p>MICRO FRONT</p>  <p>X</p>
<p>MIDGET FRONT</p>  <p>Y</p>	<p>TREADED KART CROSSBLOCK</p>  <p>Z</p>	<p>TREADED KART ANGLE BLOCK</p>  <p>aa</p>	<p>SLICK</p>  <p>bb</p>
<p>ATV FRONT - LS</p>  <p>cc</p>	<p>ATV KNOBBY</p>  <p>dd</p>	<p>TRI-TRAC</p>  <p>ee</p>	<p>ATV</p>  <p>ff</p>
<p>ATV FRONT - HP</p>  <p>gg</p>	<p>WIDE TRI-TRAC</p>  <p>hh</p>		

TIRE TREADS

TIRE TREADS

# Hoosier<sup>®</sup>

## RACING TIRE

**“TIRES DESIGNED FOR CHAMPIONS”<sup>®</sup>**

# TABLE OF CONTENTS

LEAD #	TIRE	PAGE #
	<b>NO WARRANTY POLICY &amp; WARNINGS</b> .....	Inside Front Cover
	DIRECTION OF ROTATION/MOUNTING	
	INSTRUCTIONS .....	1
	Tread Patterns .....	2-3
39/40	ARCA .....	5
41	Little Car Asphalt/Mini-Cup.....	5
13	Midget Asphalt .....	5
08/10/37	Asphalt Short Track.....	5-6
08/09	Modified/Supers/Sprint/Silver Crown Asphalt.....	6-7
12	Oval Track D.O.T. Dirt .....	7
36	Late Model/E-Mod/Street Stock Dirt .....	7-9
14	Eastern Modified/358/Sportsman Dirt .....	9
31/38	Wing Sprint Dirt .....	9-10
31	Non-Wing Sprint Dirt/Silver Crown Short Track Dirt.....	10
31	Silver Crown Dirt/Mile Tracks.....	10
35	Midget Dirt/Mini Sprint .....	11
42	Modified Midget/Micro Sprint Dirt/Jr. Sprint .....	11
11	Dirt Oval Karting .....	11
11	Treaded Kart .....	12
15	Asphalt Oval Karting.....	12
15	Asphalt Quarter Midget .....	12
11	Dirt Quarter Midget.....	12
22	Sprint/Road Race Kart/Super Kart .....	12
	4 Cycle Sprint Kart.....	13
	Enduro Kart .....	13
16/42	ATV .....	13
17	Quick Time D.O.T.....	13
17	Quick Time Pro D.O.T.....	14
18	Drag Racing .....	14-15
18	JR Dragster.....	15
28/32	Racing Tubes & Liner .....	15
17	D.O.T. Drag Radials.....	16
43	Road Racing Slicks – Bias .....	16
43	Road Racing Slicks – Radial .....	17
44	Road Racing Wets – Bias.....	17
44	Road Racing Wets – Radial .....	18
45	Sports Car D.O.T. – Bias .....	18
44/45/46	Vintage & Historic.....	18
46	Sports Car D.O.T. – Radial.....	19
46	Sports Car D.O.T. – Radial Wet .....	20
19	Pro Street D.O.T. – Radial.....	20
	<b>Hoosier Racing Tire Distributors</b> .....	Back Cover

**SEE WARNINGS STARTING ON INSIDE COVER**

*Tire rule spec tires may not be listed in this catalog. Please contact local distributor for further information.*

REV. 11/10  
First Printing

# ARCA

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
40310	11.0/88.015 Bias Dirt	L	11.0"	28.0"	88.0"	9.5"	9.5"	13.5"	D45L, D70R (Dirt Track)
39100	11.0/28.0R-15 Radial L	bb	10.7"	27.8"	87.3"	9.5"	9.5"	12.75"	25 (Short Track Radial -L)
39200	11.0/28.0R-15 Radial R	bb	10.7"	28.2"	88.6"	9.5"	9.5"	12.75"	40 (Short Track Radial -R)
*	12.0/28.0R-15 Radial L	bb	12.0"	27.8"	87.3"	9.5"	9.5"	13.2"	Speedway Left
*	12.0/28.0R-15 Radial L	bb	12.0"	28.0"	87.75"	9.5"	9.5"	13.2"	Talladega / Daytona Left
*	12.0/28.0R-15 Radial R	bb	12.0"	28.2"	88.6"	9.5"	9.5"	13.2"	Speedway Right

\* DETERMINED BY HOOSIER RACING TIRE CORP. PRIOR TO THE EVENT

# LITTLE CAR ASPHALT / MINI-CUP

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
41100	6.0/18.0-10	bb	6.0"	18.0"	56-57"	6-7"	7"	8.5"	LC0, LC3
41120	8.0/18.0-10	bb	8.0"	18.0"	56-57"	7-8"	8"	9.8"	LC3
41130	10.0/19.0-10	bb	10.0"	19.0"	60.0"	10"	10"	12.2"	LC5
<b>MINI-CUP</b>									
41149	15.0/ 7.0-8 SH	bb	6.25"	15.37"	48.25"		8.0"	7.5"	MC780
41150	15.0/ 7.0-8	bb	6.25"	15.75"	49.5"		8.0"	7.5"	MC780

SOFT \_\_\_\_\_ LC0 \_\_\_\_\_ LC3 \_\_\_\_\_ LC5 \_\_\_\_\_ MC780 \_\_\_\_\_ FIRM

# MIDGET ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
13109	7.0/20.5-13	bb	7.0"	20.5"	65.0"	8"	8"	8.6"	MG4, MG5, MG6, 600
13110	7.0/20.5-13	bb	7.0"	20.5"	66.0"	8"	8"	8.6"	700, DX2, MG5, MG7, MG8
13115BG06	7.0/20.5-13 BG2006	bb	7.0"	20.5"	66.0"	8"	8"	8.6"	BG2006
13195	10.0/22.0-13	bb	9.0"	22.0"	68.0"	8"	8"	11.2"	500, DX1, FOCUS, MG5
13196	10.0/22.5-13	bb	10.0"	22.5"	69.0"	8"	8"	11.2"	MG5
13205	10.0/23.0-13	bb	10.0"	23.0"	70.0"	8"	8"	11.6"	MG5
13206	10.0/23.0-13	bb	10.0"	23.0"	71.0"	8"	8"	11.6"	MG6
13210	10.0/23.5-13	bb	10.0"	23.5"	73.0"	10"	10"	11.6"	760, DX3, FOCUS
13220	12.0/23.5-13	bb	12.0"	23.5"	74.0"	10-12"	10"	13.5"	MG7.3
13240	12.0/23.5-13	bb	12.0"	23.5"	74.0"	10-12"	10"	13.5"	MG7
13246	12.0/23.5-13	bb	12.0"	23.5"	74.0"	10"	10"	13.5"	MG7.8
13248	12.0/23.5-13	bb	12.0"	23.5"	74.0"	10"	10"	13.5"	MG8.5

SOFT \_\_\_\_\_ 500 \_\_\_\_\_ 600 \_\_\_\_\_ 700 \_\_\_\_\_ 760 \_\_\_\_\_ FIRM

MG4 MG5 MG6 MG7 MG7.3 MG8 DX3 FOCUS R MG8.5  
DX1 FOCUS L DX2

# ASPHALT SHORT TRACK

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
08600	27.0/10.0-15 SX	bb	10.0"	26.5"	83.0"	10"	10"	13.2"	1030, 1040
08625	27.0/10.0-15 MED	bb	10.0"	27.0"	85.5"	10"	10"	13.2"	1030
08650	27.0/10.0-15	bb	10.0"	27.5"	86.0"	10"	10"	13.2"	1040, 1050
10050	8.0/23.0-13	bb	8.0"	23.5"	73.8"	8"	8"	10.2"	F60, Sportsman, TUSA
10051	8.0/23.0-13 SH	bb	8.0"	23.0"	72.5"	8"	8"	10.2"	F60, Sportsman, TUSA
10060	22.5/ 7.0-13	H	7.0"	22.5"	70.7"	6"	6"	8.6"	SPORTMAN
10070	23.0/ 7.0-13	H	7.0"	23.0"	72.2"	6"	6"	8.6"	SPORTMAN, SUPER TD
10144	10.0/27.0-15 SX	bb	10.0"	26.5"	83.0"	10"	10"	13.2"	1055, 1058
10160	10.0/27.0-15 SH	bb	10.0"	27.0"	84.8"	10"	10"	13.2"	1070
10170	10.0/27.0-15	bb	10.0"	27.5"	86.0"	10"	10"	13.2"	1070
10172	10.0/27.0-15	bb	10.0"	27.5"	86.0"	10"	10"	13.2"	1055, 1058
10175	27.0/10.0-15 SX	bb	10.0"	26.5"	83.0"	10"	10"	13.2"	2040
10177	27.0/10.0-15 SH	bb	10.0"	27.0"	84.8"	10"	10"	13.2"	2035, 2045, 2060
10179	27.0/10.0-15	bb	10.0"	27.5"	86.0"	10"	10"	13.2"	2040, 2045, 2070

OVAL TRACK ASPHALT

OVAL TRACK ASPHALT

# ASPHALT SHORT TRACK CON'T.

OVAL TRACK ASPHALT

OVAL TRACK ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
10186	27.0/ 8.0-15 SX	bb	8.0"	26.8"	84.0"	8"	8"	11.5"	2040
10188	27.0/ 8.0-15 MED	bb	8.0"	27.3"	86.0"	8"	8"	11.4"	2040, 2070
10196	9.0/26.5-15	bb	9.0"	26.5"	84.0"	10"	10"	12.5"	400, 500
10198	9.0/27.0-15	bb	9.0"	27.0"	86.5"	10"	10"	12.75"	600, 700
10220	26.5/ 8.0-15	H	8.0"	26.5"	82.1"	8"	8"	10.2"	SPORTSMAN, COMANCHE
10230	27.5/ 8.0-15	H	8.0"	27.5"	85.3"	8"	8"	10.7"	SPORTSMAN, COMANCHE
10240	23.0/ 7.0-13 RIB	ii	6.6"	22.75"	71.5"	7"	7"	9.3"	700, 800
10245	23.5/ 7.0-13 RIB	ii	6.6"	23.2"	73.0"	7"	7"	9.1"	700, 800
10260	23.5/ 7.0-14 RIB	ii	6.6"	23.15"	72.75"	7"	7"	8.8"	700, 800
10265	24.0/ 7.0-14 RIB	ii	6.6"	24.1"	75.75"	7"	7"	9.2"	700, 800
10280	26.5/ 8.0-15 RIB	R	8.0"	26.5"	82.0"	8"	8"	10.75"	700, 800
10285	27.0/ 8.0-15 RIB	R	8.0"	27.0"	84.5"	8"	8"	11.25"	700, 800
10290	27.5/ 8.0-15 RIB	R	8.0"	27.5"	85.5"	8"	8"	11.25"	700, 800
10295	8.0/26.5-15	H	9.0"	26.5"	83.2"	8"	8"	11.0"	970
10300	8.0/26.5-15	H	9.0"	27.0"	84.0"	8"	8"	11.0"	970
10350	8.0/27.0-15	H	9.0"	27.5"	86.3"	8"	8"	11.0"	970
10400	23.0/ 7.0-13	H	7.0"	23.0"	72.2"	6"	6"	8.6"	790
10405	23.0/ 7.0-14	H	7.0"	23.0"	72.2"	6"	6"	8.6"	790
10408	24.0/ 7.0-14	H	7.0"	24.0"	75.0"	6"	6"	9.1"	790
10410	26.5/ 7.0-15	H	7.0"	26.4"	83.0"	6"	6"	9.1"	790
10415	27.0/ 7.0-15	H	7.0"	27.0"	85.0"	6"	6"	9.2"	790
10420	26.5/ 8.0-15	H	8.0"	26.5"	82.1"	8"	8"	10.2"	880, 890
10425	27.5/ 8.0-15	H	8.0"	27.5"	85.3"	8"	8"	10.7"	880, 890
10499	26.5/ 8.0-15	bb	8.0"	26.8"	84.0"	8"	8"	11.5"	950
10500	26.5/ 8.0-15	bb	8.0"	26.8"	84.0"	8"	8"	11.5"	980
10504	27.5/ 8.0-15	bb	8.0"	27.3"	86.0"	8"	8"	11.4"	960
10505	27.5/ 8.0-15	bb	8.0"	27.3"	86.0"	8"	8"	11.4"	980
10580	26.5/ 8.0-15 RIB	ii	8.0"	26.5"	82.0"	8"	8"	10.75"	S650
10585	27.0/ 8.0-15 RIB	ii	8.0"	27.0"	84.5"	8"	8"	11.25"	S650
10590	27.5/ 8.0-15 RIB	ii	8.0"	27.5"	85.5"	8"	8"	11.25"	S650
10600	26.5/10.0-15	bb	10.0"	26.8"	84.0"	10"	10"	13.2"	F40
10610	27.0/10.0-15	bb	10.0"	27.1"	85.0"	10"	10"	13.2"	F40
10620	27.5/10.0-15	bb	10.0"	27.3"	86.5"	10"	10"	13.2"	F50
10700	27.0/10.0-15 SX	bb	10.0"	26.8"	84.0"	10"	10"	13.2"	3025, 3035
10720	27.0/10.0-15	bb	10.0"	27.3"	86.5"	10"	10"	13.2"	3035, 3045
10900	27.0/10.0-15	bb	10.0"	27.0"	84.0"	10"	10"	13.2"	ASALMS35
10920	27.5/10.0-15	bb	10.0"	27.5"	85.5"	10"	10"	13.2"	ASALMS45
37130	8.0/27.0-15 L	bb	8.0"	26.8"	84.0"	8"	8"	11.5"	F45, F53, F75
37139	8.0/27.0-15 MED	bb	8.0"	27.0"	85.0"	8"	8"	11.2"	F53, F75
37140	8.0/27.0-15	bb	8.0"	27.3"	86.0"	8"	8"	11.4"	F53, F75
37160	10.0/23.0-13 SH	bb	10.0"	22.4"	70.5"	10"	10"	12.5"	F15, F35
37170	10.0/23.0-13	bb	10.0"	23.0"	72.0"	10"	10"	12.5"	F15, F35, F45
37181	10.0/27.0-15 SX	bb	10.0"	26.8"	84.0"	10"	10"	13.2"	F45
37188	10.0/27.0-15	bb	10.0"	27.3"	86.5"	10"	10"	13.2"	F56
37190	10.0/27.0-15	bb	10.0"	27.3"	86.5"	10"	10"	13.2"	F45

SOFT

1030  
F15

1040  
3025

1050  
1055  
950

400  
3035  
2035

TUSA  
F60  
SUPER TD  
2045

500  
F45  
F40  
2060  
S650

3045  
960  
F53  
2040  
1058

600

970

1070

2070

880

980

F75

SPORTSMAN

700

F56

F50

800

COMANCHE

790

890

ST TD

FIRM

# MODIFIED/SUPERS/SPRINT ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
08400	25.5/13.0-15	bb	13.0"	25.5"	80.5"	14-15"	15"	16.4"	2020, M30
08410	26.0/13.0-15	bb	13.0"	26.0"	81.5"	14-15"	15"	16.4"	M20, M30, M45
08420	27.0/13.0-15	bb	13.0"	26.8"	84.0"	15"	15"	16.4"	M30, M45
08710	13.0/26.0-15	bb	13.0"	26.0"	81.5"	15"	15"	16.4"	1320

# MODIFIED/SUPERS/SPRINT ASPHALT CON'T.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
08720	13.0/27.0-15	bb	13.0"	26.8"	84.0"	15"	15"	16.4"	1330
09110	10.0/25.0-15	bb	10.0"	25.0"	79.0"	10"	10"	12.0"	M45
09120	11.0/24.0-15	bb	11.0"	24.0"	76.0"	10"	10"	13.0"	M10, 2010
09121	11.0/24.0-15	bb	11.0"	24.0"	76.0"	12"	12"	13.0"	2030
09125	11.0/24.5-15	bb	11.0"	24.5"	77.5"	10"	10"	12.5"	M45, M50, M60, 2045
09130	12.0/25.0-15	bb	12.0"	25.0"	78.0"	10-12"	12"	14.5"	M45, 2045
09142	13.0/25.0-15	bb	13.0"	25.0"	78.0"	13-14"	13"	15.0"	2045
09180	15.0/25.0-15	bb	15.0"	25.0"	79.0"	15-16"	15"	16.4"	M30
09193	26.5/13.0-15 (SC1)	bb	13.0"	26.5"	82.5"	14"	14"	16.4"	M30
09194	27.0/13.0-15 (SC1)	bb	13.0"	27.0"	83.0"	14"	14"	16.4"	M30
09200	17.0/28.0-15	bb	17.0"	27.7"	86.5"	18"	18"	20.0"	2045
09204	17.0/28.0-15 (SC1)	bb	17.0"	27.7"	86.5"	18"	18"	20.0"	M50
09205	17.0/28.0-15 (SC2)	bb	17.0"	27.7"	86.5"	18"	18"	20.0"	M49
09208	17.0/28.0-15	bb	17.0"	27.7"	86.5"	18"	18"	20.0"	2048
09209	17.0/28.0-15 (SC1)	bb	17.0"	27.7"	86.5"	18"	18"	20.0"	M55

SOFT

FIRM

M10 2010	M20 2020 1320	M30 2030 1330	M45 2045	2048	M49	M50	M55
-------------	---------------------	---------------------	-------------	------	-----	-----	-----

# OVAL TRACK D.O.T. DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
12100	P195/65D-13	V	7.0"	23.3"	73.0"	6-7"	6"	8.5"	MED
12130	P205/60D-13	V	8.0"	22.6"	71.0"	7-8"	7"	9.1"	MED
12150	P215/60D-13	V	8.0"	23.3"	73.0"	7-8"	7"	9.3"	SOFT, MED
12160	P225/60D-13	V	8.0"	23.6"	74.5"	7-8"	7"	9.7"	MED
12170	P235/60D-13	V	8.0"	23.8"	75.0"	7-8"	7"	10.2"	SOFT, MED
12322	P245/60D-15	V	8.0"	26.7"	84.0"	8-9"	8"	10.6"	MED
12330	P255/60D-15	V	8.0"	27.3"	86.0"	8-9"	8"	10.7"	MED
12340	P265/60D-15	V	8.0"	28.0"	88.0"	8-9"	8"	11.1"	SOFT, MED
12352	P275/60D-15	V	10.0"	28.2"	88.5"	10-11"	10"	12.6"	MED
12360	P285/60D-15	V	10.0"	28.5"	90.0"	10-11"	10"	12.8"	SOFT, MED
12390	P305/60D-15	V	10.0"	29.0"	92.0"	10-11"	10"	13.6"	SOFT, MED

**WARNING:** DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

# LATE MODEL / E-MOD / STREET STOCK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
<b>SPEC</b>									
36019	G60-15	N	8.5"	25.5"	81.0"	8"	8"	10.75"	IMCA
36020	G60-15	N	8.5"	26.0"	82.0"	8"	8"	10.75"	IMCA
36025	22.5/10.0-13	P	10.0"	22.4"	70.5"	8-10"	8"	11.25"	1200, 1300, 1350
36031	26.5/8.0-15	L	8.5"	26.0"	82.0"	8"	8"	10.75"	DCM400
36032	27.5/8.0-15	L	8.5"	26.75"	84.0"	8"	8"	11"	DCM400
36035	23.0/10.0-13	P	10.0"	23.1"	72.5"	8-10"	8"	11.25"	1200, 1300, 1350
36040	23.0/7.0-13	L	7.0"	23.3"	73.0"	7-8"	7"	9.0"	RC3
36050	22.5/8.0-13	L	8.0"	22.6"	71.0"	7-8"	7"	9.1"	RC1
36051	8.0/22.5-13	L	8.0"	22.6"	71.0"	7-8"	7"	9.1"	100, 400
36055	23.0/8.0-13	L	8.0"	23.3"	73.0"	7-8"	7"	9.3"	RC1, RC3
36056	8.0/23.0-13	L	8.0"	23.3"	73.0"	7-8"	7"	9.3"	100, 400
36103	8.0/26.5-15	L	8.0"	26.5"	82.0"	8-9"	8"	10.5"	H 500, IMCA 500
36105	8.0/27.0-15	L	8.0"	27.0"	84.0"	8-9"	8"	10.5"	H 500, IMCA 500
36108	10.0/27.0-15	L	10.0"	27.0"	84.0"	10-11"	10"	12.5"	500
36125	8.0/84.0-15	V	8.0"	26.0"	84.0"	8-9"	8"	11.0"	D30
36135	8.0/87.0-15	V	8.0"	27.7"	87.0"	8-9"	8"	11.3"	D30
36175	26.5/8.0-15 WISSOTA	L	8.0"	26.5"	84.0"	8-9"	8"	11.2"	35

# LATE MODEL / E-MOD / STREET STOCK DIRT CON'T.

OVAL TRACK DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS	
<b>SPEC CONT.</b>										
36185	27.5/8.0-15	WISSOTA	L	8.0"	27.5"	86.0"	8-9"	8"	11.2"	35
36208	26.5/8.0-15		L	8.0"	26.5"	83.2"	8-9"	8"	11.0"	D40
36212	27.5/8.0-15		L	8.0"	27.5"	86.2"	8-9"	8"	11.2"	A40, H40, WSH40
36213	27.5/8.0-15		L	8.0"	27.5"	86.3"	8-9"	8"	11.2"	D40
36215	26.5/8.0-15		L	8.0"	26.5"	83.2"	8-9"	8"	11.0"	RC4, A40, WSH40
36216	27.5/8.0-15		L	8.0"	27.5"	86.3"	8-9"	8"	11.2"	RC4
36226	27.5/11.0-15		L	11.0"	27.0"	86.0"	10-12"	10"	13.0"	IMCA
36239	28.0/11.0-15		L	11.0"	28.0"	88.0"	10-12"	10"	13.0"	IMCA
36240	28.0/10.5-15		L	10.5"	28.0"	88.0"	10-12"	10"	13.0"	RC3, RC4
36310	29.0/10.5-15		L	10.5"	29.0"	91.0"	10-12"	10"	13.5"	RC3, RC4, RC6
36316	29.0/11.0-15		L	11.0"	29.0"	91.0"	10-12"	10"	13.5"	IMCA
36608	88.0/11.0-15		W	11.0"	27.8"	87.5"	12-14"	14"	15.5"	FT200, FT400
36610	88.0/11.0-15		W	11.0"	28.0"	88.0"	12-14"	12"	15.5"	D21, D28, D35, D55, HTS21, HTS55
36612	88.0/11.0-15		K	11.0"	28.0"	88.0"	12-14"	12"	15.25"	WRS-2
36613	88.0/11.0-15		K	11.0"	28.0"	88.0"	12-14"	12"	15.25"	WISSOTA WRS-2
36617	UMP LM8811		P	11.0"	28.0"	87.5"	12-14"	14"	14.25"	M10, M20, M30, M40
36618	90.0/11.0-15		W	11.0"	28.2"	88.5"	12-14"	14"	15.75"	FT200, FT400
36620	90.0/11.0-15		W	11.0"	28.5"	90.0"	12-14"	12"	15.5"	D21, D28, D35, D45, D55, HTS21, HTS55
36622	90.0/11.0-15		K	11.0"	28.5"	90.0"	12-14"	12"	15.25"	WRS-2
36623	90.0/11.0-15		K	11.0"	28.5"	90.0"	12-14"	12"	15.25"	WISSOTA WRS-2
36627	UMP LM9011		P	11.0"	28.1"	88.5"	12-14"	14"	14.25"	M10, M20, M30, M40
36628	92.0/11.0-15		W	11.0"	29.3"	92.0"	12-14"	14"	15.5"	FT200, FT400, FT600
36629	92.0/11.0-15		W	11.0"	29.0"	92.0"	12-14"	12"	15.5"	WISSOTA WRS
36630	92.0/11.0-15		W	11.0"	29.0"	92.0"	12-14"	12"	15.5"	D21, D28, D35, D45, D55, HTS21, HTS55
36631	92.0/11.0-15		W	11.0"	29.0"	92.0"	12-14"	12"	15.5"	WRS
36632	92.0/11.0-15		K	11.0"	29.0"	92.0"	12-14"	12"	15.5"	WRS-2
36633	92.0/11.0-15		K	11.0"	29.0"	92.0"	12-14"	12"	15.5"	WISSOTA WRS-2
36637	UMP LM9211		P	11.0"	29.0"	92.0"	12-14"	14"	14.5"	M10, M20, M30, M40
36935	205/60-13		V	8.0"	22.6"	71.0"	7-8"	7"	9.1"	TUSA Soft
36940	215/60-13		V	8.0"	23.3"	73.0"	7-8"	7"	9.3"	TUSA Soft, TUSA Medium
36945	235/60-13		V	8.0"	23.8"	75.0"	7-8"	7"	10.2"	TUSA Soft, TUSA Medium
<b>PREMIUM SPEC</b>										
36605	28.5/11.0-15		U	11.0"	28.5"	90.5"	12-14"	14"	14.25"	1200, 1300, 1350, 1600
36606	28.5/11.0-15		U	11.0"	28.5"	90.5"	12-14"	14"	14.25"	USA21, USA55
36615	88.0/11.0-15		P	11.0"	28.0"	87.0"	12-14"	14"	14.25"	1200, 1300, 1350, 1600
36616	88.0/11.0-15		P	11.0"	28.0"	87.0"	12-14"	14"	14.25"	USA21, USA55
36625	90.0/11.0-15		P	11.0"	28.1"	88.1"	12-14"	14"	14.25"	1200, 1300, 1350, 1600
36626	90.0/11.0-15		P	11.0"	28.1"	88.1"	12-14"	14"	14.25"	USA21, USA55
36635	92.0/11.0-15		P	11.0"	29.0"	92.0"	12-14"	14"	14.25"	1200, 1300, 1350, 1600, D70
36636	92.0/11.0-15		P	11.0"	29.0"	92.0"	12-14"	14"	14.25"	USA21, USA55
<b>OPEN COMPETITION</b>										
36021	G60-15		N	8.5"	25.5"	81.0"	8"	8"	10.75"	
36022	G60-15		N	8.5"	26.0"	82.0"	8"	8"	10.75"	
36104	8.0/26.5-15		L	8.0"	26.5"	82.0"	8-9"	8"	10.5"	500
36106	8.0/27.0-15		L	8.0"	27.0"	84.0"	8-9"	8"	10.5"	500
36143	26.0/ 8.0-15		L	8.0"	26.0"	82.0"	8-9"	8"	11.0"	Soft, Med 100
36149	26.5/ 8.0-15		L	8.0"	26.5"	84.0"	8-9"	8"	11.2"	Soft, Medium, Hard, Med 100, Med 200
36155	27.5/ 8.0-15		L	8.0"	27.5"	86.0"	8-9"	8"	11.2"	Soft, Medium, Hard, Med 100, Med 200
36357	29.0/11.0-15		L	11.0"	29.5"	92.0"	12-14"	14"	16.0"	2700
36421	28.5/11.0-15		M	11.0"	28.5"	89.5"	12-14"	14"	15.5"	1200, 1300, 1325, 1350, 1400, 1425, 1450, 1600, 2400
36422	28.5/11.0-15		P	11.0"	28.5"	88.0"	12-14"	14"	15.5"	1100
36423	11.0/28.5-15		M	11.0"	28.5"	89.5"	12-14"	14"	15.5"	1600
36431	29.0/11.0-15		M	11.0"	29.0"	92.0"	12-14"	14"	15.5"	1200, 1300, 1325, 1350, 1400, 1425, 1450, 1600, 2400
36432	11.0/29.0-15		M	11.0"	29.0"	92.0"	12-14"	14"	15.5"	1600
36441	29.0/11.0-15 NRM		M	11.0"	29.4"	92.4"	12-14"	14"	15.25"	1200, 1300, 1325, 1350, 1400, 1425, 1450, 1600
36442	11.0/29.0-15 NRM		M	11.0"	29.4"	92.4"	12-14"	14"	15.25"	1600
36727	28.5/11.0-15 C4000		P	11.0"	28.5"	90.5"	12-14"	14"	14.25"	1100, 1200, 1300, 1350

# LATE MODEL / E-MOD / STREET STOCK DIRT CON'T.

OVAL TRACK DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS																																																																																																		
<b>OPEN COMPETITION CON'T.</b>																																																																																																											
36733	11.0/86.0-15	C2150	P	11.0"	28.0"	87.5"	12-14"	14"	16.25"	1100																																																																																																	
36743	11.0/88.0-15	C2150	P	11.0"	28.0"	88.5"	12-14"	14"	16.25"	1100																																																																																																	
36747	11.0/88.0-15	C4000	P	11.0"	28.0"	88.5"	12-14"	14"	16.25"	1200, 1300, 1325, 1350, 1400, 1425, 1450, 1600, 2400																																																																																																	
36781	29.0/11.0-15	C3050	P	11.0"	29.5"	92.0"	12-14"	14"	14.5"	1100																																																																																																	
36784	29.0/11.0W-15	C2000	P	11.0"	29.5"	92.0"	14.0"	14.0"	16.25"	1100																																																																																																	
36787	29.0/11.0-15		P	11.0"	29.5"	92.0"	12-14"	14"	14.5"	1200, 1300, 1325, 1350																																																																																																	
<table border="0" style="width:100%; text-align:center;"> <tr> <td colspan="3"></td> <td>D40</td> <td colspan="3"></td> <td>A40</td> <td colspan="2"></td> <td>WRS-2</td> <td>H40</td> </tr> <tr> <td colspan="3"></td> <td>D21</td> <td>D28</td> <td>D35</td> <td>D45</td> <td colspan="2"></td> <td>USA55</td> <td>D55</td> <td>IMCA</td> </tr> <tr> <td colspan="3"></td> <td>1350</td> <td>2400</td> <td></td> <td>1450</td> <td colspan="2"></td> <td>2500</td> <td>WRS</td> <td>2700</td> </tr> <tr> <td>SOFT</td> <td colspan="3">TUSA Soft</td> <td>USA21</td> <td colspan="2">TUSA Med</td> <td colspan="2">TUSA</td> <td colspan="2">HARD</td> <td>500</td> <td>FIRM</td> </tr> <tr> <td>1100</td> <td>1200</td> <td>1300</td> <td>1325</td> <td colspan="2">1400</td> <td>1425</td> <td colspan="2"></td> <td>1500</td> <td>1600</td> <td>D70</td> <td></td> </tr> <tr> <td colspan="3"></td> <td>RC1</td> <td colspan="2"></td> <td>RC3</td> <td colspan="2">RC4</td> <td colspan="3"></td> </tr> <tr> <td colspan="3">M10</td> <td>SOFT</td> <td>MED 100</td> <td colspan="2">MED 200</td> <td colspan="2">MEDIUM</td> <td colspan="3">M40</td> </tr> <tr> <td colspan="3"></td> <td>M20</td> <td colspan="2"></td> <td>M30</td> <td colspan="5"></td> </tr> </table>													D40				A40			WRS-2	H40				D21	D28	D35	D45			USA55	D55	IMCA				1350	2400		1450			2500	WRS	2700	SOFT	TUSA Soft			USA21	TUSA Med		TUSA		HARD		500	FIRM	1100	1200	1300	1325	1400		1425			1500	1600	D70					RC1			RC3	RC4					M10			SOFT	MED 100	MED 200		MEDIUM		M40						M20			M30					
			D40				A40			WRS-2	H40																																																																																																
			D21	D28	D35	D45			USA55	D55	IMCA																																																																																																
			1350	2400		1450			2500	WRS	2700																																																																																																
SOFT	TUSA Soft			USA21	TUSA Med		TUSA		HARD		500	FIRM																																																																																															
1100	1200	1300	1325	1400		1425			1500	1600	D70																																																																																																
			RC1			RC3	RC4																																																																																																				
M10			SOFT	MED 100	MED 200		MEDIUM		M40																																																																																																		
			M20			M30																																																																																																					

# EASTERN MODIFIED / 358 / SPORTSMAN DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS																														
<b>SPEC</b>																																							
14131	11.0/82.0-15SH	L	10.5"	25.5"	80.5"	10-12"	10"	12.0"	D200, D300, D400																														
14133	11.0/82.0-15	L	10.5"	26.0"	82.0"	10-12"	10"	12.0"	D300, D400																														
14135	11.0/87.0-15	L	11.0"	27.2"	85.5"	10-12"	12"	14.2"	M45, D50																														
14143	11.0/90.0-15SH	L	11.0"	28.0"	88.5"	10-12"	12"	14.2"	M45, D50																														
14145	11.0/90.0-15	L	11.0"	29.0"	90.5"	10-12"	12"	14.5"	M45, D60																														
14151	13.0/82.0-15	L	13.0"	26.3"	82.0"	12-14"	13"	14.0"	D200, D300, D400, D500																														
14178	13.0/87.0-15	L	13.0"	27.5"	86.0"	12-14"	14"	16.2"	D200, D300, D400																														
14190	13.0/89.0-15	L	13.0"	28.0"	88.0"	12-14"	14"	16.2"	D200, D300, D400																														
14225	13.0/92.0-15	L	13.0"	29.0"	91.5"	12-14"	14"	16.5"	D200, D300, D400, D500																														
14226	13.0/92.0-15Tall	L	13.0"	29.5"	92.5"	12-14"	14"	16.5"	D200, D300, D400																														
<b>OPEN COMPETITION</b>																																							
14475	26.5/11.0-15	L	10.0"	26.5"	84.5"	10-12"	12"	12.5"	H70																														
14525	27.5/13.0-15	L	13.0"	27.5"	86.0"	13-14"	13"	16.0"	D20																														
14550	28.0/13.0-15	L	13.0"	28.0"	88.0"	13-14"	13"	16.2"	D20, H60																														
14625	29.0/13.0-15	L	13.0"	29.5"	92.5"	14"	14"	16.5"	D45, H70																														
<table border="0" style="width:100%; text-align:center;"> <tr> <td>SOFT</td> <td colspan="3">Soft</td> <td colspan="3">Hard</td> <td colspan="2">Extra</td> <td>FIRM</td> </tr> <tr> <td>D200</td> <td>D300</td> <td>M45</td> <td>D50</td> <td>D400</td> <td>D60</td> <td colspan="2">D500</td> <td colspan="2">H70</td> </tr> <tr> <td colspan="2">D20</td> <td colspan="2">D45</td> <td colspan="2">H60</td> <td colspan="4"></td> </tr> </table>										SOFT	Soft			Hard			Extra		FIRM	D200	D300	M45	D50	D400	D60	D500		H70		D20		D45		H60					
SOFT	Soft			Hard			Extra		FIRM																														
D200	D300	M45	D50	D400	D60	D500		H70																															
D20		D45		H60																																			

# WING SPRINT DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
31131	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D10, D12
31132	85.0/ 8.0-15	L	8.0"	27.0"	85.0"	8"	8"	10.5"	D15, D20
31135	86.0/ 8.0-15	L	8.5"	27.0"	85.0"	8"	8"	10.7"	F25, F35
31149	88.0/15.0-15	T	15.0"	28.0"	88.0"	14-15"	15"	18.6"	D10
31159	90.0/15.0-15	T	15.0"	28.5"	90.0"	14-15"	15"	18.0"	D10, RD12
31169	92.0/15.0-15	T	15.0"	29.0"	92.0"	14-15"	15"	18.5"	D10, RD12, D12
31189	94.0/15.0-15	T	15.0"	30.0"	94.0"	14-15"	15"	18.3"	D10, RD12, D12, RD15, D15, D20
31191	94.0/15.0-15	T	15.0"	29.7"	93.5"	14-15"	15"	18.3"	D10, RD12, D12
31209	96.0/15.0-15	T	15.0"	30.5"	96.0"	14-15"	15"	18.7"	D10, RD12, D12, RD15, D15
31242	98.0/15.0-15	T	15.0"	31.5"	98.0"	14-15"	15"	18.5"	D12
31303	105.0/18.0-15	T	18.0"	32.2"	105.0"	16-18"	18"	21.5"	D10, RD12, D12, RD15, D15, RD20, D25
38221	105.0/16.0-15	T	16.0"	33.0"	104.0"	16-18"	17"	20.3"	MED
38123	88.0/14.0-15	T	15.0"	28.0"	88.0"	14-15"	14"	18.0"	MED

## WING SPRINT DIRT CON'T.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
38133	90.0/14.0-15	T	15.0"	28.5"	90.0"	14-15"	14"	18.0"	MED
38135	90.0/14.0-15	T	15.0"	28.5"	90.0"	14-15"	14"	18.0"	RC1
38143	92.0/14.0-15	T	15.0"	29.0"	92.0"	14-15"	14"	18.0"	MED, IMCA
38146	92.0/14.0-15	T	15.0"	29.0"	92.0"	14-15"	14"	18.0"	RC1
38153	94.0/14.0-15	T	15.0"	30.0"	94.0"	14-15"	14"	18.0"	MED
38156	94.0/14.0-15	T	15.0"	30.0"	94.0"	14-15"	14"	18.0"	RC1
38162	96.0/14.0-15	T	15.0"	30.5"	96.0"	14-15"	14"	18.5"	RC1, MED
38172	102.0/16.0-15	S	15.0"	32.5"	102.0"	15-17"	16"	19.3"	RC3, VRA, IMCA
38230	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	HTC, NRA
38231	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	Hard
38250	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	SC12, SCRD15, SC15, SC25

			RC1	HTC						
			SC12	SCRD15	SC15	NRA			SC25	
SOFT	D10	RD12	D12	RD15	D15	RD20	D20		D25	FIRM
					F35	MED		DT3	HARD, IMCA	
								RC3	VRA	

## NON-WING SPRINT/SILVER CROWN SHORT TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
31131	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D10, D12
31132	85.0/ 8.0-15	L	8.0"	27.0"	85.0"	8"	8"	10.5"	D15, D20
31135	86.0/ 8.0-15	L	8.5"	27.0"	85.0"	8"	8"	10.7"	F25, F35
31183	92.0/14.0-15	T	15.0"	29.0"	92.0"	14"	14"	18.0"	D10
31203	94.0/14.0-15	T	15.0"	30.0"	94.0"	14"	14"	18.0"	D10
31225	96.0/14.0-15	T	15.0"	30.5"	96.0"	14"	14"	18.5"	RD12
31227	96.0/14.0 W-15	T	16.0"	30.5"	97.0"	15"	15"	19.0"	RD12
31237	98.0/14.0-15	T	15.0"	31.5"	98.0"	14"	14"	18.5"	RD12, D12
31239	98.0/14.0 W-15	T	16.0"	31.5"	99.0"	15"	15"	19.0"	RD12
31247	100.0/13.0-15	S	13.2"	31.8"	101.0"	14"	14"	17.2"	D25
31249	100.0/13.0-15	S	13.2"	31.8"	100.0"	14"	14"	17.2"	D12
31303	105.0/18.0-15 C-2055	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	D10, RD12, D12, RD15, D15, RD20, D25
38215	104.0/17.0-15	S	17.0"	33.0"	103.5"	16-18"	18"	21.0"	DT3

SOFT	D10	RD12	D12	RD15	D15	RD20	D20	D25, DT3	F55	FIRM
			F25		F35					

## SILVER CROWN DIRT / MILE TRACKS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
<b>DIRT ONLY</b>									
31132	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D20, F75
31256	103.0/14.0-15	T	14.5"	32.1"	101.0"	14"	14"	18.5"	D50, F55
31303	105.0/18.0-15 C2055	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	F85, F95

SOFT										FIRM
				D20	D50	F55	F75	F85	F95	



## TREADED KART

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
11900	11.0 x 5.5-6	aa	5.5"	11.0"	35.0"	6-6.5"	6.5"	6.5"	D10, D20A, D30
11940	12.0 x 8.0-6	Z	8.0"	12.0"	38.0"	9-10"	10.0"	9.75"	D10, D20A, D30
11960	12.0 x 9.0-6	Z	9.0"	12.0"	39.0"	9-10"	10.0"	10.25"	D10, D20A, D30, D50, D55

## ASPHALT OVAL KARTING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
15300	10.5 x 4.5-6	bb	4.5"	10.5"	33"	6"	6"	6.25"	A40
15750	11.0 x 7.1-6	bb	7.25"	11.0"	34"	9"	9"	8.875"	A40
15810	11.0 x 8.1-6	bb	7.875"	11.0"	34"	10"	10"	9.75"	A40A

## ASPHALT QUARTER MIDGET

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
15151	31.0/4.5-5	bb	4.5"	10.0"	31"	5-6"	5"	5.5"	A35, A40A
15171	32.0/4.5-5	bb	4.5"	10.25"	32"	5-6"	5"	5.5"	A35, A40A
15175	32.5/4.5-5	bb	4.5"	10.25"	32.5"	5-6"	5"	5.5"	A35
<b>USAC</b>	<b>.25 MIDGET</b>	<b>POSITION</b>							
15325	33.0/5.0-6	RF	4.75"	10.5"	33.5"	6-6.5"	6"	6.25"	A35, A40A
15650	34.5/6.5-6	RR	6.25"	11.0"	34.75"	8-8.5"	8.5"	8.25"	A35, A40A
15751	35.0/7.1-6	Wide RR	7.00"	11.0"	35"	8-9"	9.0"	8.75"	A35, A40A

## DIRT QUARTER MIDGET

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
11050	31.0/4.5-5	bb	4.5"	10.00"	31"	5-6"	5"	5.5"	D10, D20A
11100	32.0/4.5-5	bb	4.5"	10.25"	32"	5-6"	5"	5.5"	D10, D20A
11175	33.0/5.0-6	bb	4.75"	10.50"	33.5"	6-6.5"	6"	7.25"	D10, D30
11225	34.5/6.5-6	bb	6.25"	11.00"	34.75"	8-8.5"	8.5"	8.25"	D10, D30

## SPRINT/ROAD RACE KART/SUPER KART

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
22150	4.5/10.0-5	bb	4.25"	10.0"	32"	5.0-5.5"	5.0"	5.5"	R50, R60
22250	6.0/11.0-5	bb	5.5"	11.0"	34"	7.0-7.25"	7.0"	7.25"	R50, R60
22350	7.1/11.0-5	bb	6.75"	11.0"	34"	8.0-8.25"	8.25"	8.50"	R50, R60
22700	5.0/10.5-6	bb	4.25"	10.5"	33.5"	6"	6.0"	6.75"	R50, R60
22855	7.1/11.0-6	bb	7.0"	11.0"	35"	8"	8.0"	8.25"	R50, R60
22900	8.0/11.0-6	bb	7.25"	11.0"	35.5"	8.5-9"	8.5"	8.75"	R50, R60



# QUICK TIME PRO D.O.T.

QUICK TIME

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
17411	26 X 9.50-14 LT	D	8.0"	26.1"	82.0"	6-8"	8"	10.0"	Quick Time Pro
17415	26 X 9.50-15 LT	D	8.0"	26.1"	82.0"	6-8"	8"	9.9"	Quick Time Pro
17421	26 X 11.50-15 LT	D	10.0"	26.4"	83.0"	8-10"	8"	11.5"	Quick Time Pro
17431	26 X 9.50-16 LT	D	8.0"	26.1"	82.0"	6-8"	8"	9.3"	Quick Time Pro
17500	27 X 10.50-15 LT	D	9.0"	27.0"	85.0"	8-10"	8"	10.1"	Quick Time Pro
17510	27 X 11.50-15 LT	D	10.0"	27.0"	85.0"	8-10"	8"	11.2"	Quick Time Pro
17601	28 X 11.50-15 LT	D	10.0"	28.0"	88.0"	8-10"	8"	11.2"	Quick Time Pro
17603	28 X 11.50-16 LT	D	10.0"	28.0"	88.0"	8-10"	10"	11.8"	Quick Time Pro
17606	28 X 13.50-15 LT	D	11.0"	28.0"	88.0"	10-12"	10"	12.9"	Quick Time Pro
17611	28 X 14.50-15 LT	D	12.0"	28.0"	88.0"	10-12"	10"	13.1"	Quick Time Pro
17651	28 X 14.50-16 LT	D	12.0"	28.0"	88.0"	10-12"	10"	12.9"	Quick Time Pro
17700	29 X 11.50-15 LT	D	10.0"	29.3"	92.0"	8-10"	8"	11.9"	Quick Time Pro
17705	29 X 13.50-15 LT	D	11.0"	29.3"	92.0"	10-12"	10"	13.4"	Quick Time Pro
17710	29 X 14.50-15 LT	D	12.0"	29.3"	92.0"	10-12"	10"	13.9"	Quick Time Pro
17790	31 X 13.50-15 LT	D	11.0"	30.9"	97.0"	10-12"	10"	14.1"	Quick Time Pro
17800	31 X 16.50-15 LT	D	13.0"	30.9"	97.0"	12-14"	12"	16.0"	Quick Time Pro
17810	31 X 18.50-15 LT	D	15.0"	30.9"	97.0"	14-15"	14"	17.9"	Quick Time Pro
17900	33 X 18.50-15 LT	D	15.0"	33.0"	104.0"	14-15"	14"	18.5"	Quick Time Pro
17910	33 X 22.50-15 LT	D	17.0"	33.0"	104.0"	15-16"	15"	20.0"	Quick Time Pro
17950	35 X 22.50-16 LT	D	17.0"	35.0"	110.0"	15-16"	16"	21.5"	Quick Time Pro

SOFT Quick Time Pro Quick Time Ft. FIRM

**WARNING:** DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

# DRAG RACING

DRAG RACING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
<b>Drag Front</b>									
18085	23.0/ 5.0-15	B	4.8"	23.0"	72.0"	3.5-4"	3.5"	5.8"	Drag Front
18095	24.0/ 5.0-15	B	4.8"	23.8"	75.0"	3.5-4"	3.5"	6.2"	Drag Front
18102	25.0/ 5.0-15	B	4.8"	24.8"	77.9"	3.5-4"	3.5"	6.7"	Drag Front
18105	26.0/ 4.5-15	B	4.3"	25.8"	81.0"	3.5-4"	3.5"	6.5"	Drag Front
18106	27.0/ 4.5-15	B	4.5"	27.0"	85.0"	3.5-4"	4"	7.2"	Drag Front
18107	28.0/ 4.5-15	B	4.5"	27.7"	87.0"	3.5-4"	4"	7.5"	Drag Front
18108	22.0/ 2.5-17	A	1.5"	22.0"	69.0"	2.5"	2.5"	2.7"	Dragster Front
<b>Drive Tires - Slicks</b>									
18060	24.5/ 8.0-13	C	7.8"	24.3"	76.0"	6-8"	7"	9.7"	D06
18110	26.0/ 8.0-15	C	8.0"	26.1"	82.0"	7-8"	8"	9.7"	D06
18115	26.0/ 8.5-15	C	9.0"	26.1"	82.0"	7-8"	8"	10.3"	C11
18120	26.0/ 9.0-15	C	9.0"	26.1"	82.0"	7-8"	8"	10.3"	D06
18131	26.0/10.0-15	C	10.0"	26.2"	82.0"	8-10"	9"	11.0"	D06
18140	28.0/ 9.0-15	C	9.0"	28.0"	88.0"	8-10"	8"	11.1"	D06
18150	28.0/10.0-15	C	10.0"	28.0"	88.0"	8-10"	8"	11.7"	D06
18153	28.0/10.0-16	C	10.0"	28.0"	88.0"	8-10"	10"	12.0"	C07
18155	28.0/10.5-15*	C	10.2"	28.0"	88.0"	8-10"	8"	12.0"	C07
18157	28.0/10.0-17	C	9.5"	28.0"	88.0"	8-10"	8"	11.3"	D06
18160	29.0/ 9.0-15	C	9.0"	29.1"	91.5"	8-10"	8"	11.4"	D06, D07
18170	29.0/10.0-15	C	10.0"	29.1"	91.5"	8-10"	8"	11.9"	D06
18175	29.0/10.5-15 W*	C	11.0"	29.3"	92.0"	8-10"	10"	13.2"	D06
18180	29.0/11.0-15	C	11.0"	29.3"	92.0"	8-10"	10"	13.2"	D06
18190	29.0/12.0-15	C	12.0"	29.3"	92.0"	10-12"	10"	13.7"	D06
18192	29.5/10.5-15	C	11.1"	30.6"	96.0"	10-12"	10"	13.2"	D06
18194	10.5/29.5-15	C	10.5"	30.0"	94.0"	10-12"	10"	13.1"	C11
18195	29.5/11.5-15 W*	C	13.5"	30.6"	96.0"	12-14"	12"	15.2"	D06

# DRAG RACING CONT.

DRAG RACING

DRAG RACING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
18200	30.0/ 9.0-15	C	9.0"	30.0"	94.0"	8-10"	8"	11.8"	D05, D07
18205	30.0/10.5-15	C	10.5"	30.0"	94.0"	8-10"	10"	13.1"	D05
18209	30.0/9.0R-15 Radial***	C	9.0"	29.5"	92.5"	8-10"	8"	11.3"	C06
18210	30.0/9.0R-15 Radial	C	9.0"	29.5"	92.5"	8-10"	8"	11.3"	C07
18211	9.0/30.0R-15 Radial	C	9.0"	29.9"	94.0"	8-10"	8"	11.3"	C07
18212	9.0/30.0R-15 Radial***	C	9.0"	29.9"	94.0"	8-10"	8"	11.3"	C06
18214	30.0/10.5R-15 Radial***	C	10.5"	29.5"	92.5"	9-10"	10"	12.5"	C06
18215	30.0/10.5R-15 Radial	C	10.5"	29.5"	92.5"	9-10"	10"	12.5"	C07
18221	31.0/10.5-15	C	11.0"	30.8"	97.0"	10-12"	12"	14.7"	C07
18235	31.5/12.5-15 W*	C	13.5"	31.7"	99.5"	12-14"	14"	17.2"	D05
18237	13.5/31.5-15 L***	C	13.5"	31.7"	99.5"	12-14"	14"	17.2"	C07
18239	31.5/13.5R-15 Radial	C	13.5"	31.8"	99.7"	14-15"	14"	16.9"	C06
18240	31.0/14.0-15	C	14.0"	31.2"	98.0"	12-14"	12"	16.5"	D05
18242	32.0/12.0-15	C	12.2"	32.0"	101.0"	10-12"	12"	15.8"	D05
18243	32.0/13.0-15	C	13.2"	32.0"	101.0"	12-13"	12"	16.9"	D05
18245	32.0/13.5-15 W*	C	14.0"	32.3"	102.0"	12-14"	14"	16.9"	D05
18247	32.0/13.5R-15 Radial	C	13.5"	32.2"	101.2"	14-15"	14"	17.0"	C06
18250	32.0/14.0-15	C	14.0"	32.3"	102.0"	12-14"	14"	17.7"	D05
18255	14.0/32.0-15 L***	C	14.0"	32.3"	102.0"	12-14"	14"	17.8"	C07
18260	32.0/14.5-15 W*	C	15.0"	32.6"	102.5"	14-15"	14"	18.4"	D05
18265	14.5/32.0-15 L***	C	15.0"	32.3"	102.0"	14-15"	14"	18.4"	C07
18267	32.0/14.5R-15 Radial	C	15.0"	32.2"	101.2"	14-16"	14"	18.1"	C06
18280	32.0/17.0-15	C	17.2"	32.3"	102.0"	15-16"	16"	20.7"	D06
18300	32.5/16.5-15	C	16.7"	32.3"	101.5"	15-16"	15"	19.8"	C07
18332	33.0/10.5-15 Outlaw	C	11.5"	33.0"	104.0"	10-12"	12"	15.6"	C11
18336	10.5/33.0-16 Outlaw	C	11.5"	33.4"	105.0"	14-16"	15"	17.3"	C11
18350	33.0/12.0-15	C	12.2"	33.0"	102.0"	10-12"	10"	15.2"	C09
18361	33.0/14.5R-15 Radial	C	15.0"	33.0"	104.0"	14-16"	14"	18.4"	C06
18367	14.5/33.0-15 L***	C	14.5"	33.0"	104.0"	14-15"	14"	18.2"	C07
18370	33.0/15.0-15	C	15.0"	33.0"	104.0"	14-15"	14"	18.7"	D05
18400	33.0/16.0-15	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	D05, D06, C07
18450	33.0/16.5-15 S**	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	D06, C07
18500	33.0/17.0-16	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	C07
18600	33.5/16.0-15	C	17.0"	33.6"	106.0"	15-16"	15"	19.8"	C07
18640	33.5/16.5-16 S**	C	17.0"	33.6"	106.0"	15-16"	16"	19.9"	C07
18650	33.5/17.0-16	C	17.0"	33.6"	106.0"	15-16"	16"	19.9"	C07
18700	33.5/17.0-16	C	17.0"	33.6"	106.0"	15-16"	16"	20.7"	C06
18780	17.0/34.5-16	C	17.0"	35.0"	110.0"	15-16"	16"	20.5"	C2055
18790	34.5/17.0-16	C	17.0"	35.0"	110.0"	15-16"	16"	21.4"	C2055
18800	34.5/17.0-16	C	17.0"	35.0"	110.0"	15-16"	16"	21.4"	C4000
18900	36.0/17.0-16	C	17.0"	36.2"	114.0"	15-16"	16"	21.7"	C2055
18975	12.00-16	C	12.0"	33.0"	105.0"	10-12"	12"	16.2"	N/TF

SOFT	JR3	C06 C07	C11	Drag Front	FIRM
	D05	D06	D07	N/TF C09	

\* STIFF SIDEWALL  
 \*\* SOFT SIDEWALL  
 \*\*\* LIGHTWEIGHT

# JR DRAGSTER

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
18030	18.0/ 8.0-8	C	7.7"	17.7"	55.5"	7-8"	8"	9.9"	JR3
18040	18.0/ 10.0-8	C	9.5"	17.7"	55.5"	8-10"	8"	10.6"	JR3

# RACING TUBES & LINER

ITEM NUMBER	TUBE SIZE	TREAD WIDTH
288088-15	80/ 88-15 TUBE	6" TO 11" TREAD WIDTH
2886100-15	86/100-15 TUBE	11" TO 13" TREAD WIDTH
2894106-15	94/106-15 TUBE	15" TO 19" TREAD WIDTH
32400	75/16.0-16 LINER	FOR USE WITH ITEM NUMBERS 18780, 18790, 18800, 18900



# ROAD RACING SLICKS – RADIAL

ROAD RACING SLICKS

ROAD RACING SLICKS

ITEM NUMBER	TIRE SIZE		APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
43540	20.5 X 7.0R13		F2000	7.2"	21.0"	66.0"	6"	6"	8.4"	
43545	22.5 X 9.0R13		F2000	9.2"	22.6"	71.0"	8"	8"	9.8"	
43547	200/580R15		RADICAL	8.0"	22.9"	71.9"	6.5-8"	8"	8.8"	R35A, R45B
43557	215/580R15			8.6"	22.9"	71.8"	7-9"	7"	9.7"	R80, R100
43567	245/580R15			9.4"	22.9"	71.8"	7-10"	7"	10.0"	R80, R100
43570	23.0 X 9.5R15		FA	9.4"	22.9"	72.0"	10"	10"	10.7"	R25B, R35A
43585	23.5 X 13.0R15		FA	13.0"	23.5"	73.8"	14"	14"	14.5"	R25B, R35A
43590	27.5 X 11.5R15		HSCF	11.5"	27.4"	86.0"	10"	9.5"	12.8"	
43595	27.5 X 11.5R15		HSCR	11.5"	27.4"	86.0"	10"	9.5"	12.8"	
43655	23.5 X 11.0R16		GT2	10.6"	23.6"	74.0"	10"	10"	11.0"	R75
43660	23.5 X 12.0R16		GT2	12.0"	23.5"	73.8"	12"	12"	13.0"	R75
43662	265/605R16		RADICAL	9.7"	23.9"	75.1"	9-10"	10"	10.9"	R35A, R45B
43671	25.5 X 12.5R16	C2000	GT1	12.4"	25.8"	81.0"	12"	12"	13.3"	R75
43676	25.5 X 14.0R16	C2000	GT1	13.6"	25.7"	80.9"	12"	12"	14.1"	R75
43681	27.0 X 13.0R16	C2000	GT1	13.0"	27.3"	85.8"	13"	13"	14.6"	R75
43691	28.0 X 14.0R16	C2000	GT1	13.9"	28.2"	88.5"	13"	13"	15.1"	R75
43720	235/620R17			9.6"	24.3"	76.5"	8-9.5"	9"	9.6"	R80, R100
43735	265/630R17			10.1"	24.8"	77.9"	9-10"	10"	10.7"	R100
43815	235/645R18			8.5"	25.5"	80.0"	8-9.5"	8"	9.1"	R80
43825	250/650R18 CUP			9.1"	25.6"	80.4"	8-9.5"	9"	9.8"	R80, R100
43835	265/645R18			10.1"	25.5"	80.0"	9-10"	10"	10.9"	R80, R100
43840	280/680R18 CUP			10.0"	26.9"	84.6"	9-11"	10"	11.3"	R100
43855	285/645R18			10.9"	25.5"	80.0"	10-12"	11"	11.7"	R80, R100
43857	295/660R18			11.7"	26.9"	84.5"	10-11"	11"	12.3"	R100
43860	305/30R18 NARRA			11.6"	25.6"	80.5"	11-12"	11"	12.5"	
43865	305/645R18			11.8"	25.6"	80.6"	11-13"	12"	12.7"	R80, R100
43867	305/680R18			11.8"	27.0"	84.9"	10-12"	12"	12.9"	R100
43870	320/650R18			12"	25.8"	80.8"	11-12"	12"	13"	R100
43875	315/690R18			12.3"	27.3"	85.7"	11-12"	12"	13.5"	R100
43880	335/30R18 NARRA			12.6"	25.6"	80.5"	12-13"	12"	13.5"	
43890	310/710R18			12.5"	28.2"	88.4"	10-12"	12"	13.6"	R100
43895	355/650R18			13.8"	25.7"	80.8"	12-14"	13"	14.2"	R80, R100
43915	235/645R19			8.5"	25.5"	80.1"	8-9.5"	9"	9.5"	R80
43945	295/680R19			9.8"	26.9"	84.5"	10-12"	11"	11.7"	R100

ALL TREAD PATTERNS bb

SOFT ————— R75 ————— R80 ————— R100 ————— FIRM  
R25B ————— R35A ————— R45B

# ROAD RACING WETS – BIAS

ITEM NUMBER	TIRE SIZE	TREAD PATTERNS	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH
44125	19.5 X 6.5-10	I	F500	6.2"	19.7"	62.0"	6-8"	8"	8.2"
44140	20.0 X 6.5-13	I	FF, FM, FC, S2000, DSR	6.2"	20.7"	65.0"	6-7.5"	6"	7.0"
44150	20.0 X 7.5-13	I	CSR, FA	7.4"	20.6"	64.6"	7-8"	7"	8.3"
44165	20.0 X 8.0-13	I	FP, GP, HP, GT4, GT5	8.0"	20.5"	64.5"	6"	6"	8.8"
44185	21.0 X 6.5-13	I	FF, FM, FC, S2000, DSR	6.7"	21.2"	66.5"	6-8"	6"	7.2"
44195	21.5 X 7.5-13	I	SCCA-F, SR	7.5"	21.4"	66.8"	8.0"	8"	8.8"
44217	22.0 X 9.0-13	I	SCCA-F, SR, FC, FA, FM, S2000, DSR, CSR	8.5"	22.9"	71.8"	8.5-10"	8"	10.0"
44220	22.5 X 7.5-13	I	FF	7.5"	22.8"	71.5"	5.5-6.0"	5.5"	9.8"
44235	23.0 X 11.5-13	I	FA, CSR	11.5"	23.7"	74.5"	14-15"	14"	14.8"
44266	22.5 X 5.0-15	I	FV	5.0"	22.0"	69.2"	4"	4"	6.5"
44275	22.5 X 9.0-15	I	FA	8.8"	22.4"	70.5"	10"	10"	10.1"
44277	23.0 X 9.0-15	I	EP, GT3	8.5"	22.4"	70.5"	6-7"	7"	10.0"
44280	23.5 X 11.5-15	I	FA	11.5"	23.7"	74.5"	14"	14"	14.8"
44307	27.0 X 10.0-15	L	HSC/GTA	10.0"	27.0"	84.0"	10-11"	10"	12.5"

## ROAD RACING WETS – RADIAL

ITEM NUMBER	TIRE SIZE	TREAD PATERNS	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH
44440	20.5 X 7.0R-13 WET	J	F2000, FC	7.1"	21.0"	66.0"	6"	6"	8.3"
44445	22.5 X 9.0R-13 WET	J	F2000, FC	9.1"	22.6"	71.0"	8"	8"	9.8"
44450	23.0 X 9.5R-13	J	FA	9.5"	23.0"	72.4"	10"	10"	10.6"
44460	23.5 X 12.0R-13	J	FA	11.9"	23.5"	73.8"	14"	13"	14.0"
44590	23.0 X 9.5R-15	J	FA	9.5"	23.0"	72.4"	10"	10"	10.6"
44595	23.5 X 12.0R-15	J	FA	11.9"	23.5"	73.8"	14"	14"	14.0"
44655	23.5 X 11.0R-16	J	GT2	10.6"	23.6"	74.0"	10"	10"	11.0"
44671	25.5 X 12.5R-16 C2000	J	GT1, GT2	12.2"	25.7"	80.9"	12"	12"	13.2"
44681	27.0 X 13.0R-16 C2000	J	GT1	13.6"	27.3"	85.7"	12"	12"	14.2"

TREAD PATTERN IS HAND GROOVED.

## SPORTS CAR D.O.T. - BIAS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	STREET T.D. S	WET
45100	P185/60D-13	H	6.2"	20.6"	64.7"	5-7"	5"	7.0"	X	
45110	P205/60D-13	H	6.2"	22.4"	70.5"	5.5-7"	5.5"	7.5"	X	
45111DS	P205/60D-13*	L	6.8"	21.9"	68.8"	5.5-7.5"	5.5"	7.8"		X
45115	P225/45D-13	H	7.8"	20.8"	65.5"	6.5-8.5"	7.5"	9.0"	X	
45120	P205/60D-14	H	7.2"	23.0"	72.3"	6-8"	5.5"	8.3"	X	
45140	P225/50D-14	H	7.8"	23.0"	72.5"	7-9"	6"	8.8"	X	
45150	P205/50D-15	H	6.7"	23.0"	72.5"	5.5-7"	6"	7.6"	X	
45160	P225/45D-15	H	7.6"	23.0"	72.5"	6.5-8.5"	7.5"	8.5"	X	
45170	P225/50D-15	H	7.0"	24.0"	75.5"	6.5-8.5"	6"	8.5"	X	
45180	P225/60D-15	H	8.0"	25.8"	81.0"	7-9"	6"	9.2"	X	
45165	P245/45D-15	H	8.5"	24.0"	75.5"	7.5-9.5"	8"	10.0"	X	
45190	P245/60D-15	H	8.0"	26.4"	83.0"	7-9.5"	7"	10.0"	X	
45200	P275/60D-15	H	9.5"	27.6"	86.5"	8.5-10"	7.5"	11.0"	X	

\*DS RECOMMENDED FOR WET APPLICATION ONLY.

## VINTAGE & HISTORIC

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	MODEL
44391	165/70-10	H	5.2"	18.8"	59.0"	5-6"	5.5"	7.3"	HOOSIER T.D. S
45105	A70-13	H	6.2"	22.4"	70.3"	5-7"	5"	7.5"	STREET T.D. S
44286	25.5 X 8.5-15	H	8.7"	25.4"	79.7"	8-10"	8"	10.3"	HOOSIER T.D. S
44296	25.5 X 10.0-15	H	10.0"	25.8"	81.0"	8-11"	8"	11.2"	HOOSIER T.D. S
44306	26.5 X 9.5-15	H	9.5"	26.6"	83.5"	8-10"	8"	11.0"	HOOSIER T.D. S
44316	27.5 X 11.0-15	H	11.0"	27.7"	87.0"	10-13"	10"	13.2"	HOOSIER T.D. S
44336	24.0 X 8.5-16	H	8.2"	24.1"	75.4"	8-10"	8"	10.5"	HOOSIER T.D. S
44346	25.5 X 10.0-16	H	10.0"	25.6"	80.5"	9-11"	9"	11.3"	HOOSIER T.D. S
44400	5.00-15	L	5.2"	24.7"	77.6"	4-6"	4"	7.0"	VINTAGE T.D.
44405	120/590-15	L	4.8"	22.6"	70.9"	4.5"	4.5"	6.1"	VINTAGE T.D.
44408	135/620-15	L	5.6"	24.1"	75.6"	4.5"	4.5"	6.9"	VINTAGE T.D.
44410	5.50-15	L	6.5"	24.7"	77.6"	4.5-7"	4.5"	7.7"	VINTAGE T.D.
46006	P185/70R14	G	6.8"	24.1"	75.8"	4.5-6"	6"	7.75"	SPEEDSTER
46008	P205/65R14	G	7.5"	24.1"	75.8"	5.5-8"	6"	8.25"	SPEEDSTER
46010	P185/65R15	G	6.4"	24.2"	76.0"	5.0-6.5"	5"	7.0"	SPEEDSTER
46015	P205/60R15	G	7.3"	24.2"	76.0"	5.5-7.5"	6.5"	8.25"	SPEEDSTER

S = Stiff Sidewall

**WARNING:** DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

# SPORTS CAR D.O.T. - RADIAL

SPORTS CAR D.O.T.

SPORTS CAR D.O.T.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	A6 AUTO CROSS	R6 ROAD RACE
46300	P185/60ZR13	E	6.9"	21.7"	68.2"	6-7"	6.0"	7.8"		X
46305	P205/60ZR13	E	8.0"	22.8"	71.7"	5.5-7.5"	6.0"	8.8"		X
46307	P225/45ZR13	E	8.5"	20.9"	65.8"	7.0-8.5"	7.5"	9.3"	X	X
46310	P225/50ZR13	E	8.5"	21.9"	69.0"	6-8"	7.0"	9.4"	X	X
46320	P255/40ZR13	E	9.5"	20.9"	65.6"	8.5-10"	9.0"	10.5"	X	
46405	P205/55ZR14	E	8.1"	22.8"	71.6"	5.5-7.5"	7.0"	9.1"	X	X
46410	P205/60ZR14	E	7.8"	23.6"	74.2"	7-8"	6.0"	8.2"		X
46415	P225/50ZR14	E	8.5"	22.9"	72.0"	6-8"	7.0"	9.4"	X	X
46500	P205/50ZR15	E	8.0"	22.8"	71.7"	5.5-7.5"	6.5"	8.7"	X	X
46500	P205/50ZR15 SM6	E	8.0"	22.8"	71.7"	5.5-7.5"	6.5"	8.7"		X
46505	P215/60ZR15	E	8.3"	25.2"	79.1"	6.0-7.5"	7.0"	9.2"		X
46510	P225/45ZR15	E	9.0"	22.9"	72.0"	7.0-8.5"	7.5"	9.8"	X	X
46515	P225/50ZR15	E	8.8"	23.8"	74.8"	6-8"	7.0"	9.8"		X
46525	P245/50ZR15	E	9.2"	24.8"	78.0"	7.0-8.5"	7.5"	10.1"		X
46535	P275/35ZR15	E	10.1"	23.0"	72.2"	9.0-11.0"	9.5"	10.8"	X	X
46540	P275/50ZR15	E	10.0"	25.5"	80.0"	7.5-9.5"	8.0"	10.8"		X
46600	P205/45ZR16	E	8.0"	22.8"	71.7"	6.5-7.5"	7.0"	8.7"	X	X
46610	P225/50ZR16	E	9.0"	24.7"	77.6"	6-8"	7.0"	9.5"	X	X
46615	P245/45ZR16	E	9.2"	24.7"	77.7"	7.5-9.0"	8.0"	10.1"	X	X
46620	P255/50ZR16	E	9.4"	26.2"	82.2"	7-9"	8.0"	10.5"	X	X
46630	P275/45ZR16	E	10.3"	25.6"	80.5"	8.5-10.0"	9.0"	11.2"	X	X
46700	P205/40ZR17	E	7.0"	23.8"	74.8"	7-8"	8.0"	8.5"		X
46705	P225/40ZR17	E	8.9"	23.8"	74.5"	7-9"	7.5"	9.8"	X	X
46710	P225/45ZR17	E	8.8"	24.7"	77.7"	7.0-8.5"	7.5"	9.7"	X	X
46715	P245/40ZR17	E	9.3"	24.5"	77.0"	8.0-9.5"	8.5"	10.0"	X	X
46720	P245/45ZR17	E	9.4"	25.7"	80.7"	7.5-9.0"	8.0"	9.9"		X
46725	P255/45ZR17	E	9.7"	26.2"	82.2"	8.0-9.5"	9.0"	10.8"		X
46730	P275/40ZR17	E	10.3"	25.5"	80.1"	9.0-11.0"	9.5"	11.0"	X	X
46733	P295/35ZR17	E	10.8"	25.3"	79.5"	9.5-11.0"	10.0"	11.6"	X	X
46735	P315/35ZR17	E	11.4"	25.6"	80.4"	11-12"	11.0"	12.6"	X	X
46740	P335/35ZR17	E	12.9"	25.6"	80.5"	11-13"	12.0"	13.6"	X	X
46810	P225/40ZR18	E	8.8"	24.8"	77.8"	7.5-9.0"	8.0"	9.5"	X	X
46820	P245/35ZR18	E	9.1"	24.7"	77.7"	8.0-9.5"	8.5"	9.8"	X	X
46825	P245/40ZR18	E	9.3"	25.7"	80.6"	8.0-9.5"	8.5"	10.5"	X	X
46830	P255/40ZR18	E	9.8"	26.2"	82.1"	8.5-10.0"	9.0"	10.6"		X
46832	P255/35ZR18	E	10.3"	24.8"	77.8"	8.5-10.0"	9.0"	10.8"	X	X
46836	P275/35ZR18	E	10.3"	25.5"	80.2"	9-11"	9.5"	10.7"	X	X
46840	P285/30ZR18	E	10.9"	24.9"	78.1"	10-11"	10.0"	11.5"	X	X
46843	P295/30ZR18	E	10.8"	25.3"	79.5"	9.5-11"	10.0"	11.6"	X	X
TBA	P295/40ZR18	E	TBA							
46846	P315/30ZR18	E	11.8"	25.6"	80.5"	11-12"	11.0"	12.5"	X	X
TBA	P315/40ZR18	E	TBA							
46850	P335/30ZR18	E	12.8"	25.6"	80.5"	12-13"	12.0"	13.5"	X	X
46855	P345/35ZR18	E	13.2"	26.8"	84.2"	11-13"	12.0"	13.9"	X	X
46915	P235/35ZR19	E	9.2"	25.6"	80.5"	8.0-9.5"	9.0"	10.2"	X	X
46925	P265/35ZR19	E	9.6"	26.2"	82.25"	9-10"	9.0"	10.4"	X	X
46935	P295/30ZR19	E	10.4"	26.1"	82.1"	10-12"	10.0"	11.5"	X	X
TBA	P295/35ZR19	E	TBA							
46937	P315/30ZR19	E	12.0"	26.1"	82.2"	11-12"	11.0"	12.5"	X	X
TBA	P315/35ZR19	E	TBA							
46940	P315/40ZR19	E	11.3"	28.9"	90.7"	11-12"	11.0"	12.9"		X
46945	P325/30ZR19	E	12.2"	26.8"	84.1"	12-13"	13.0"	13.6"	X	X
46950	P345/30ZR19	E	13.0"	26.8"	84.3"	12-13"	13.0"	14.1"	X	X

**WARNING:** DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

## SPORTS CAR D.O.T. RADIAL WET

ITEM NUMBER	TIRE SIZE	SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH
46105	P205/60R13	86H	J	7.1"	23.5"	73.8"	6-7.5"	6.0"	8.5"
46115	P205/55R14	85H	J	7.1"	23.5"	73.8"	6.5-7.5"	6.5"	8.7"
46125	P205/50R15	84H	J	7.1"	23.5"	73.8"	6.5-7.5"	6.5"	8.2"
46130	P225/55R15	92H	J	8.8"	24.8"	77.9"	7-8"	7.0"	9.4"
46135	P205/45R16	77H	J	7.1"	23.5"	73.8"	7-7.5"	7.0"	8.4"
46140	P225/50R16	91H	J	8.8"	24.8"	77.9"	7-9"	7.0"	9.6"
46145	P245/45R16	88H	J	9.0"	24.8"	77.9"	7-9"	8.0"	10"
46150	P255/50R16	99H	J	9.3"	26.3"	82.5"	8-9"	8.0"	10.7"
46170	P225/45R17	84H	J	8.8"	24.8"	77.9"	8-9"	7.5"	9.5"
46175	P245/40R17	86H	J	9.0"	24.8"	77.9"	7-9"	8.0"	10"
46177	P245/45R17	89H	J	9.0"	25.5"	80.1"	7-9"	8.0"	10"
46185	P275/40R17	93H	J	10.0"	25.2"	79.2"	9-11"	9.5"	11.3"
46190	P315/35R17	93H	J	11.8"	25.6"	80.4"	11-12"	11"	12.7"
46200	P225/40R18	83H	J	8.8"	24.8"	77.9"	7-9"	8"	9.9"
46205	P245/35R18	80H	J	9.0"	24.8"	77.9"	7-9"	8"	10"
46207	P245/40R18	88H	J	8.75"	25.5"	80.25"	8-9.5"	9.0"	9.75"
46210	P255/40R18	90H	J	9.3"	26.3"	83.0"	9-10"	9.0"	10.5"
46215	P275/35R18	87H	J	10.0"	25.2"	79.2"	10-11"	9.5"	11.3"
46220	P305/30R18	89H	J	11.8"	25.6"	80.4"	11-12"	11"	12.7"

**WARNING:** DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

**NOTE:** H Speed Rating = 130 mph/210 km/h.

## PRO STREET D.O.T. RADIAL

ITEM NUMBER	TIRE SIZE	SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	MAX. LOAD	RATED INF. PSI	MODEL
<b>Fronts</b>												
19030	24 X 7.50R-15 LT	71H	F	5.3"	23.8"	73.3"	5-6.5"	6"	7.5"	760	35	Pro Street
19040	25 X 7.50R-15 LT	75H	F	5.3"	24.9"	76.9"	5-6.5"	6"	7.5"	855	35	Pro Street
19050	26 X 7.50R-15 LT	79H	F	5.3"	25.9"	80.5"	5-6.5"	6"	7.5"	965	35	Pro Street
19055	26 X 7.50R-17 LT	74H	F	5.3"	25.9"	80.5"	5-6.5"	6"	7.5"	825	35	Pro Street
19075	27 X 10.50R-15 LT	88H	F	8.3"	26.5"	82.8"	7-9.0"	8.5"	10.5"	1235	35	Pro Street
19100	28 X 9.50R-15 LT	90H	F	8.0"	27.0"	85.0"	7.5-9.0"	8.0"	9.75"	1325	35	Pro Street
19150	29 X 12.50R-15 LT	89H	F	10.0"	29.0"	90.8"	8.5-11"	10"	13.0	1280	25	Pro Street
19200	29 X 15.50R-15 LT	91H	F	12.1"	29.0"	91.5"	11-13"	12"	15.2"	1355	25	Pro Street
19215	29 X 15.50R-16 LT	89H	F	12.1"	29.0"	91.8"	11-13"	12"	15.2"	1280	25	Pro Street
19250	29 X 18.50R-15 LT	93H	F	14.6"	29.0"	91.3"	13-16"	14"	17.8"	1435	25	Pro Street
19275	31 X 12.50R-15LT	95H	F	10.3"	31.0"	96.5"	8.5-11"	10"	13.4"	1520	25	Pro Street
19276	31 X 12.50R-16 LT	93H	F	10.3"	31.0"	96.5"	8.5-11"	10"	12.8"	1435	25	Pro Street
19300	31 X 16.50R-15 LT	98H	F	12.8"	31.0"	96.3"	12-14"	12"	16.0"	1655	25	Pro Street
19315	31 X 16.50R-16 LT	96H	F	12.8"	31.0"	96.8"	12-14"	12"	16.0"	1565	25	Pro Street
19325	31 X 16.50R-17 LT	94H	F	12.8"	31.0"	96.8"	12-14"	12"	16.0"	1475	25	Pro Street
19350	31 X 18.50R-15 LT	99H	F	14.5"	31.0"	96.3"	13-16"	14"	18.0"	1710	25	Pro Street
19375	31 X 18.50R-17 LT	95H	F	14.5"	31.0"	96.3"	13-16"	14"	18.0"	1520	25	Pro Street
19410	33 X 21.50R-15 LT	107H	F	16.8"	32.0"	100.8"	15-19"	17"	21.3"	2150	25	Pro Street

**WARNING:** "Pro Street Tires are designed for highway use and are not suitable for racing purposes."

**NOTE:** H Speed Rating = 130 mph / 210 km/h

# Hoosier<sup>®</sup>

RACING TIRE

Contact Your Hoosier Tire  
Distributor Today!



Visit Your Local Hoosier Tire Distributor To See the  
NEW 2011 High Performance Racing Tires  
and Apparel Line Up!



Racing has been a part of our lives for over 50 years! Watching Americans come to embrace the excitement of the track – while experiencing the rise of the sport to the forefront, has been a thrill and an honor we feel fortunate to have been a part of.

We proudly present our high performance racing tires and our apparel and accessories catalog in hopes that these quality products will help you show winning Hoosier spirit everywhere you go!

On behalf of the Hoosier Racing family,  
thanks for your support and enthusiasm.

*Bob & Joyce Newton*

**“TIRES DESIGNED FOR CHAMPIONS”<sup>®</sup>**

65465 U.S. 31 • Lakeville, IN 46536 • (574) 784-3152 • Fax: (574) 784-2385 • [www.hoosiertire.com](http://www.hoosiertire.com)

©2010 Hoosier Racing Tire Corp., Printed in U.S.A., All rights reserved.



# Hoosier<sup>®</sup>

## RACING TIRE

### CORPORATE

65465 U.S. 31 ♦ Lakeville, IN 46536  
(574) 784-3152 ♦ Fax: (574) 784-2385  
[www.hoosiertire.com](http://www.hoosiertire.com)

### YOUR HOOSIER TIRE DISTRIBUTOR

#### Hoosier<sup>®</sup>

TIRE EAST

56-H Loomis Street ♦ Manchester, CT 06042  
Phone: (860) 646-9646 ♦ Fax: (860) 646-2054  
E-mail: [robhte@sbcglobal.net](mailto:robhte@sbcglobal.net)

#### Hoosier<sup>®</sup>

TIRE SOUTH

Asphalt  
P.O. Box 537 ♦ Welcome, NC 27374  
Phone: (336) 731-6100 ♦ Fax: (336) 731-6086  
E-mail: [hoosierasp@lexcominc.net](mailto:hoosierasp@lexcominc.net)

#### Hoosier<sup>®</sup>

TIRE MIDWEST

Springfield  
3886 E. State Route 54 ♦ Springfield, IL 62707  
Phone: (217) 522-1955 ♦ Fax: (217) 522-6097  
E-mail: [kathy@racetires.com](mailto:kathy@racetires.com)

#### Hoosier<sup>®</sup>

TIRE MID-ATLANTIC

Baltimore  
2931 Industrial Park Drive ♦ Finksburg, MD 21048  
Phone: (410) 833-2061 ♦ Fax: (410) 833-5921  
E-mail: [sales@hoosiermidatlantic.com](mailto:sales@hoosiermidatlantic.com)

#### Hoosier<sup>®</sup>

TIRE SOUTHWEST

103 Gross Road, Bldg. A ♦ Mesquite, TX 75149  
Phone: (972) 289-RACE (7223) ♦ Fax: (972) 289-8055  
E-mail: [tomlorenz@smileysracing.com](mailto:tomlorenz@smileysracing.com)

#### Hoosier<sup>®</sup>

TIRE SOUTH

Road & Drag ♦ P.O. Box 290 ♦ Louisville, TN 37777  
Phone: (865) 984-3232 ♦ Fax: (865) 681-0775  
E-mail: [road&drag@hoosiertiresouth.com](mailto:road&drag@hoosiertiresouth.com)

#### Hoosier<sup>®</sup>

TIRE SOUTH

Dirt Oval  
504 Frank Diggs Road ♦ Clinton, TN 37717  
Phone: (865) 457-9888 ♦ Fax: (865) 457-8033  
E-mail: [hoosiertiresouth@charterinternet.com](mailto:hoosiertiresouth@charterinternet.com)

#### Hoosier<sup>®</sup>

TIRE MIDWEST

Indianapolis  
4155 North 1000 E., Suite A ♦ Brownsburg, IN 46112  
Phone: (317) 858-1234 ♦ Fax: (317) 858-1307  
E-mail: [hoosiertireindy@yahoo.com](mailto:hoosiertireindy@yahoo.com)

#### Hoosier<sup>®</sup>

TIRE MID-ATLANTIC

Pittsburgh  
110 South Pike Road, #207 ♦ Sarver, PA 16055  
Phone: (724) 360-8000 ♦ Fax: (724) 360-8044  
E-mail: [sales@hoosiermidatlantic.com](mailto:sales@hoosiermidatlantic.com)

#### Hoosier<sup>®</sup>

TIRE CANADA-NY

1733 Maryland Avenue  
Niagara Falls, New York 14305  
Phone: (716) 285-7502 ♦ Fax: (800) 285-1454  
E-mail: [usasales@bicknellracingproducts.com](mailto:usasales@bicknellracingproducts.com)

#### Hoosier<sup>®</sup>

TIRE GREAT PLAINS

3801 W. Pawnee, Suite 200 ♦ Wichita, KS 67213  
Phone: (316) 945-4000 ♦ Fax: (316) 945-4003  
E-mail: [sales@hoosiertiregp.com](mailto:sales@hoosiertiregp.com)

#### Hoosier<sup>®</sup>

TIRE WEST

2608 E. California ♦ Fresno, CA 93721  
Phone: (559) 485-4612 ♦ Fax: (559) 485-4632  
E-mail: [racing@hoosiertirewest.com](mailto:racing@hoosiertirewest.com)

#### Hoosier<sup>®</sup>

TIRE MIDWEST

Plymouth  
1801 Jim Neu Drive ♦ Plymouth, IN 46563  
Phone: (574) 936-8344 ♦ Fax: (574) 936-1673  
E-mail: [hoosiertireply@aim.com](mailto:hoosiertireply@aim.com)

#### Hoosier<sup>®</sup>

TIRE OHIO VALLEY

1933 Staunton Turnpike ♦ Parkersburg, WV 26104  
Phone: (304) 428-5000 ♦ Fax: (304) 485-8038  
1-800-430-7223 ♦ E-mail: [todd@poske.com](mailto:todd@poske.com)

#### Hoosier<sup>®</sup>

TIRE NORTH

21601 John Deere Lane ♦ Rogers, MN 55374  
Phone: (763) 428-8780 ♦ Fax: (800) 555-8577  
E-mail: [htnrace@aol.com](mailto:htnrace@aol.com)

### YOUR INTERNATIONAL HOOSIER TIRE DISTRIBUTOR

#### Hoosier<sup>®</sup>

TIRE AUSTRALIA

17 Blind Road ♦ Nelson NSW, Australia 2765  
Phone: (61) 296791990 ♦ Fax: (61) 296791187  
E-mail: [mdimport@bigpond.net.au](mailto:mdimport@bigpond.net.au)

#### Hoosier<sup>®</sup>

TIRE CANADA

117-119 Cushman Road  
St. Catharines, Ontario, Canada L2M6S9  
Phone: (905) 685-3184 ♦ Fax: (800) 891-0521  
E-mail: [brp@cogeco.net](mailto:brp@cogeco.net)

#### Hoosier<sup>®</sup>

TIRE NEW ZEALAND

32 William Pickering Drive  
Albany, Auckland ♦ New Zealand  
Phone: (09) 4151388 ♦ Fax: (09) 4150788  
E-mail: [8@cardwells.co.nz](mailto:8@cardwells.co.nz)

#### Hoosier<sup>®</sup>

TIRE WESTERN CANADA

5601-45 ST ♦ Leduc, Alberta, Canada T9E7B1  
Phone: (780) 986-7223 ♦ Fax: (780) 986-5267  
E-mail: [tim@geeandgeeracing.com](mailto:tim@geeandgeeracing.com)

#### Hoosier<sup>®</sup>

TIRE U.K.

P.O. Box 380 ♦ Horley Surrey, RH6 0WW  
United Kingdom  
Phone: +44 (0) 1293 863579  
Fax: +44 (0) 1293 863574  
E-mail: [andyhoosiertire@hotmail.com](mailto:andyhoosiertire@hotmail.com)

In addition to Australia, Canada, New Zealand and the United Kingdom, Hoosier Racing Tire Corp. has locations in Italy, Guatemala, Norway, Puerto Rico, Singapore/Malaysia, South Africa, Sweden and the United Arab Emirates. Contact information for these locations can be found on [www.hoosiertire.com](http://www.hoosiertire.com). To learn more about purchasing Hoosier tires in areas not listed, you can e-mail us at [international@hoosiertire.com](mailto:international@hoosiertire.com).

**“TIRES DESIGNED FOR CHAMPIONS”<sup>®</sup>**